

Amendments to the Claims

Please amend the claims as indicated below.

1. (Currently amended) A data collection system comprising:
 - a) a plurality of telemetry devices, each telemetry device including:
 - i) a sensor configured to generate a series of successive measurements by measuring a parameter at a series of measurement times,
 - ii) a memory configured to store a plurality of measurements from said series of successive measurements, and
 - iii) a transmitter configured to transmit measurements stored in memory to a collection device at a series of transmission times; and
 - b) a plurality of collection devices, there being fewer collection devices than telemetry devices, each collection device including:
 - i) a hub to receive transmissions as packets from selected ones of the plurality of telemetry devices, the transmissions containing both old measurements and new measurements; and
 - ii) a network device to forward at least a subset of a series of said transmissions over an internet connection to a data processing center to generate an output function.
2. (Cancelled).
3. (Original) The data collection system of claim 1, wherein said network device further comprises an internet interface.
4. (Original) The data collection system of claim 3, wherein said Internet interface further comprises an e-mail client a Hypertext Transmission Protocol (HTTP) server, and a telnet daemon.
5. (Original) The data collection system of claim 1, further comprising an e-mail server.

6. (Original) The data collection system of claim 1, wherein said sensor comprises:

a counter to store a value;
means for incrementing said counter upon receipt of a trigger signal; and
means for storing said value from said counter in said memory and resetting said counter at said measurement times.

7. (Original) The data collection system of claim 1, wherein said telemetry device further comprises a first timer having a predetermined time interval, wherein the expiration of said predetermined time interval causes said sensor to generate a measurement.

8. (Original) The data collection system of claim 1, wherein said hub comprises a radio-frequency local area network (LAN) transceiver.

9. (Original) The data collection system of claim 1, wherein said hub a radio-frequency local area network (LAN) receiver.

10. (Original) The data collection system of claim 1, wherein said hub comprises a power line carrier LAN transceiver.

11. (Original) The data collection system of claim 1, wherein said network device is electronically connected to a hub.

12. (Original) The data collection system of claim 1, wherein the network device is serially connected to the hub using Recommended Standard-232 (RS232).

13. (Original) The data collection system of claim 1, wherein said parameter is selected from the group consisting of electrical power, fluid flow, voltage, current, temperature, pressure and humidity.

14. (Original) The data collection system of claim 1, wherein the series of measurements are selected from the group consisting of pulse count, an analog voltage, a current level, and a multi-byte digital value.

15. (Previously presented) The data collection system of claim 1, wherein the data processing center forwards one or more commands through the internet connection to the hub.

16. (Original) The data collection system of claim 15, wherein the one or more commands contain configuration information.

17. (Previously presented) The data collection system of claim 15, wherein the hub passes the one or more commands to a subset of the plurality of telemetry devices.

18-27. (Deleted).

28. (Previously presented) A network device connected to a receiving device configured to collect data generated by a plurality of sensors, comprising:

a micro-processor to process data generated by the plurality of sensors and collected by the receiving device, including time-stamping and filtering;

at least one storage device to store at least a subset of processed data;

a transmitter to transmit data through an internet connection to a data processing center; and

an HTTP server to host at least one web page that displays the collected data.

29. (Original) The network device of claim 28, wherein the receiving device comprises a transceiver.

30. (Original) The network device of claim 28, wherein the receiving device comprises a receiver.

31. (Original) The network device of claim 28, wherein the network device is connected to the receiving device using a serial port.

32. (Original) The network device of claim 28, wherein the transmitter transmits data to the internet via an Ethernet connection.

33. (Original) The network device of claim 28, wherein the transmitter transmits data to the internet via a wireless Internet Protocol (IP).

34. (Original) The network device of claim 28, wherein the transmitter transmits data to the internet via a dial-up PPP connection.

35. (Original) The network device of claim 28, further comprising a multiplexer to route data between the micro-processor and the transmitter.

36. (Original) The network device of claim 28, wherein the network device is permanently connected to the internet.

37. (Original) The network device of claim 28, wherein the network device is connected to the internet by a dial-up PPP connection through a ISP.

38. (Cancelled).

39. (Original) The network device of claim 28, wherein the device hosts at least one web page to display data generated by the plurality of sensors.

40. (Original) The network device of claim 28, wherein the device is installed in a location behind a corporate firewall.

41. (Previously presented) A network device configured to collect data generated by a plurality of sensors, comprising a computer program, residing on the device, the computer program comprising instructions for causing the device to:

interface with a LAN device, the LAN device receiving data from the plurality of sensors;

display data on at least one web page;

store and forward data received by the LAN device; and

interface an internet connection to transmit data to a remote center.

42. (Original) The network device of claim 41, wherein the instruction to interface with the LAN device further comprises instructions to:

detect arrival of data from the plurality of sensors;

process that data; and

send commands from the remote center to the LAN device.

43. (Original) The network device of claim 41, wherein the instructions to process the data further comprise instructions to trigger an e-mail containing the processed data.

44. (Original) The network device of claim 41, wherein the instructions to interface the network connection comprise instructions to send data through an e-mail client.

45. (Original) The network device of claim 41, wherein the instructions to interface the network connection comprise instructions to send data a HTTP server in response to a request.

46. (Original) The network device of claim 41, wherein the instructions to interface the network connection comprise instructions to send data through a telnet daemon in response to a request.

47. (Currently amended) A data collection system, comprising:

a plurality of sensors residing in a plurality of meters, each of the plurality of sensors

being configured to sample a parameter value at discrete measurement times and including a transmitter configured to transmit measured data; ~~and~~

a plurality of collectors, each collector having a receiver configured to receive data transmitted by the plurality of sensors, a processor configured to filter and store data received by the receiver from the plurality of sensors, and a transmitter configured to transmit the filtered data as packets to a monitoring station for processing by an internet connection; and an HTTP server connected to host at least one web page displaying the received data.

48. (Original) The data collection system of claim 47, wherein the monitoring station processes the filtered data to compute electricity usage information.

49. (Currently amended) A data collection system, comprising:
a plurality of sensor means residing in a plurality of meters, each of the plurality of sensor means located near a consumer of electricity for measuring data relating to consumer usage of electricity and for transmitting the measured electricity usage data; ~~and~~

a collector means having a receiver for receiving electricity usage data transmitted by the plurality of sensor means, a processor for computing electricity usage information from electricity usage data received by the receiver, a transmitter for transmitting the electricity usage information to a remote center through an internet connection, and

an HTTP server for hosting at least one web page displaying the received data.

50. (Original) The data collection system of claim 49, wherein the plurality of measurement sensor means measures data relating to consumer usage of gas and for transmitting the measured gas data.

51. (Currently amended) A network for collecting data generated by a plurality of sensors, comprising:

- a) a plurality of data generating devices including:
 - i) a sensor to measure a parameter to generate measurements,
 - ii) a memory configured to store said measurements, and
 - iii) a transmitter to transmit said stored measurements to an intermediate device at a plurality of transmission times; ~~and~~
- b) a plurality of intermediate devices, there being fewer intermediate devices than data generating devices, said intermediate devices including:

- i) a receiver to receive transmission from a subset of said plurality of data generating devices,
 - ii) a processor to filter said measurements from said transmissions and analyze said measurements to generate a metered function of the parameter,
 - iii) a transmission module to transmit the metered function over an internet connection; and
 - iv) an HTTP server to host at least one web page displaying said measurements; and
- c) a data station remote from the plurality of intermediate devices to receive transmitted meter functions from said plurality of intermediate devices.

52. (Previously presented) A method of collecting data comprising the steps of:

- a) generating measurements by measuring a parameter using a telemetry device;
- b) storing a plurality of said measurements in a memory;
- c) transmitting said stored measurements and an alignment time from said telemetry device to a collection device;
- d) displaying said measurements on at least one web page hosted by the collection device;
- e) processing said transmitted measurements at the collection device, including a step of determining from said alignment time the measurement time of the most recent measurement in the transmission; and
- f) transmitting, under a plurality of trigger conditions, said processed measurements as packets to a monitoring station by an internet connection.

53. (Original) The method of claim 52, wherein the processing step further comprises filtering said transmitted measurements and storing the filtered measurements.

54. (Original) The method of claim 52, further comprising the step of computing a metered function representing consumption information at the monitoring station.

55. (Original) The method of claim 52, further comprising the steps of:
storing an old number in said collection device;
generating a new number in said telemetry device for each generated measurement;
and

comparing said old number to said new number to determine which measurements are new measurements not previously received by said collection device and whether there are missing measurements.

56. (Original) The method of claim 55, further comprising the step of storing said old number in said telemetry device, wherein the step of generating said new number includes incrementing said old number.

57. (Original) The method of claim 56, further comprising the step of determining the measurement times for new measurements received by said collection device.

58. (Original) The method of claim 52, further comprising the step of waiting an alignment time following a measurement to transmit said stored measurements.

59. (Original) The method of claim 58, further comprising the step of:
transmitting said alignment time from said telemetry device to said collector in a transmission;

determining a receipt time representing the time said collector receives said transmission; and

subtracting said alignment time from said receipt time to generate a time representing the measurement time of the most recent measurement in the transmission.

60. (Original) The method of claim 52, wherein said parameter is selected from the group consisting of electrical power, fluid flow, voltage, current, temperature, pressure, and humidity.

61. (Previously presented) A method of collecting data comprising the steps of:
receiving a series of successive measurements from a series of transmissions from a plurality of telemetry devices;

storing and filtering the series of successive measurements by a pathway device connected to a LAN transceiver capable of receiving the series of transmissions; and
transmitting the filtered data as packets through an internet connection to a remote center for generation of a metered output function at the remote center; and

displaying the transmitted data on at least one web page hosted by the pathway device.

62. (Original) The method of Claim 61, wherein the remote center comprises a data processing center.

63. (Original) The method of Claim 61, wherein the remote center comprises a customer site.